


A / TOP




SPECIFICATIONS

Weight capacity: 5 passengers / 1,280 lbs.
 Max HP: 15 HP / 110 lbs / Short shaft (15")
 Hull weight: 165 lbs.
 Air chambers: 5 + keel
 Fabric: Hypertex
 Factory warranty: 3 years recreational / 1 year commercial

SEC FEATURES

- 1.- A Aluminum floor with anodized aluminum stringers
- 2.- A Inflation and over inflation valves (one for each air chamber)
- 3.- A 6 carry handles, non slip design
- 4.- A 2 seat (2 positions)
- 5.- A 11 interior tie down D-rings (Stainless steel)
- 6.- A Non-skid traction covering on aluminum floor panels
- 7.- A Interior/Exterior lifelines (Peripheral)
- 8.- A Reinforcement on tube transom attachments
- 9.- A Interior transom lifting rings (Stainless steel)
- 10.- A Transom eyes
- 11.- A Two large D-rings on rear tubes (Stainless steel)
- 12.- B Interior aluminum engine mounting plate
- 13.- B Marine plywood transom
- 14.- B Standard self bailer with plug (Pop-up design)
- 15.- C All around rub strake, flat profile, black
- 16.- C Bow handle (Stainless)
- 17.- C Two large tow rings on bow (Stainless steel)
- 18.- C Rubbing strakes for beaching on keel


B / BACK



C / SIDE



ACCESSORIES



SHIPPING INFORMATION




BOAT

- Package dimensions: 46x25x18 (0.26 cbm.)
- Package weight: 202 lbs.

OPTIONAL EQUIPMENT:

- Quick-Fill field inflation system (SCUBA or SCBA)
- Scuppers set (High volume water drainage)
- Solas reflective panels (High night visibility)

ALUMINUM FLOOR



CORRECT LOCKED POSITION

- SECTIONS
- 1.- Stringers
 - 2.- Aluminum section

